

Description

Treadmaster TM8 is a synthetic rubber firesafe safety floor covering made of a coloured compound, mixed with multi-coloured speckles of the same material which provides excellent anti-slip properties.

Fire Properties

Property	Test Method	Result
EN45545-2 Classification		HL3
BS6853 PCTV Category		1a
Reaction to Fire	NFF 16-101/102	F1 M2
Surface Spread of Flame	BS476-7	Class 2
Smoke Density (A_0 max)	BS6853 D.8.6	107
Toxicity of Combustion	BS6853 annex B	R < 2
Surface Flammability	IMO res A653	CFE > 18.7
Smoke and Toxicity	IMO res. MSC 61	Ds(251)=96 Ds(250)=462 Ds(500)=133

Physical Properties

Property	Test Method	Result
Sheet Size (max)	Width / Length	2 x 12m
Hardness, °IRHD	ISO 48	80 - 90°
Density, g/cm ³	ISO 2781	1.65
Tensile Strength, MPa	ASTM F152	3.5
Flexibility	ASTM F147	3d
Abrasion Resistance	Taber Abrader 3000 cycles, 500g	Weight loss 0.6g Thickness loss 0.15mm
Slip Resistance	TRRL Pendulum	Dry 91 Wet 29
Residual Indentation	BS EN 12104	2%

Information in this document and otherwise supplied to users is based on our general experiences and is given in good faith but, because of particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or implied with respect to such information. Specifications are subject to change without notice. Statements of operating limits quoted in this document are not an indication that these values can be simultaneously applied. A safe handling data sheet on this material is available on request.